17" (16.0" VIS) Design Line Real Flat monitor



Dare to compare - LightFrame TM 3 for the sharpest and brightest displays ever!

- LightFrame™3 2 x Normal Brightness
- 17-inch (16.0" VIS) Real Flat color monitor with excellent front of screen performance for use with MACs and PCs
- Autoscan covers horizontal frequencies up to 71 kHz offering a maximum resolution of 1280 x 1024 with flicker free display of 1024 x 768 at up to 89 Hz
- Real Flat High Brightness, High Contrast CRT with high-resolution 0.25 mm dot pitch (0.21 hdp)
- World's shortest 17-inch Real Flat monitor with maximum depth of only 424 mm/16.7"
- TCO '03 certified



















17" (16.0" VIS) Desigh Line Real Flat monitor



Technical Specifications

CRT panel

Size (inch/cm)
 Deflection angle (degrees)
 Dot pitch
 Horizontal pitch
 17"/ 41 cm
 90°
 0.25 mm
 0.21 mm

-Tube type Shadow mask, Real Flat, High Brightness,
High Contrast, Anti Glare, Anti Static,
Anti reflection, Light Transmission 45%

Phosphor P22

Recom. display area(mm)
 Recom. display area(inch)
 Max. display area(mm)
 Max. display area(inch)
 Max. display area(inch)
 306 x 230 mm
 12.0" x 9.0"
 325 x 244 mm
 12.8" x 9.6"

Scanning

Horizontal scanning
 Vertical scanning
 30 - 71 kHz
 50 - 160 Hz

Video

Video dot rate
 120 MHz

· Input impedance

-Video 75 Ohm
-Sync 2.2k Ohm
Input signal levels 0.7 Vpp
Sync input signal Separate sync Composite sync
Sync polarities Positive and negative

White color temperature

Chromaticity CIE coordinates

• at 9300 K: x=0.283, y=0.297 • at 6500 K: x=0.313, y=0.329

Resolution & preset modes

• Max. resolution 1280 \times 1024 • Recom. resolution 1024 \times 768

8 user definable modes14 factory preset modes

H.freq (KHz) V.freq (Hz) 640 x 350 70 31.5K 640 x 350 37.9K 85 640 x 480 37.9K 72 640 x 480 37.5K 75 640 x 480 50.6K 100 720×400 37.9K 85 800 x 600 37.9K 60 800 x 600 48.1K 72 63.9K 800×600 100 832×624 49.7K 75 60 1024×768 48.4K 1024×768 56.5K 70 75 1152×864 67.5K 1280 x 1024

Plug and play compatibility

- Display Data Channel DDC 2B (VESA)
- Microsoft® Windows® 95/98/Me & 2000/NT/XP compatible
- sRGB

Power management

Complies with EPA Energy Star and NUTEK specifications

• Operation 68 W (typical)

• Off mode/Deep Sleep < 1 W

Low-emission characteristics

Complies with MPR-II and TCO '03 specifications



Monitor controls and functions

Main
 3-button OSD with LightFrame™

Hotkey

Brightness +/- direct access Contrast+/- direct access

On Screen Display Language (English, Spanish, French,

German, Italian, Chinese, Portuguese, Korean), zoom, horizontal, vertical, pincushion, balanced, trapezoid, paral lelogram, color, reset, degauss, moire, serial number, resolution, frequency,

sRGB

- LightFrame $^{\text{TM}}$ 3 For improving the picture display of

multi media content such as photos, videos and games. Will boost brightness and sharpness

performance on user selected areas/ windows on the screen. With automatic detection of graphical content in Internet Explorer for the web browsing. Can process up to 16

web browsing. Can process up to 16 images simultaneously.
One-button full screen mode.
Advanced user adjustments via
Windows control panel. Easy to use control software for Windows 98,Me.
XP and 2000. Software in English,
French, German, Spanish, Italian,
Portuguese, Dutch, Chinese and Korean

Connections and cables

Connections on monitor body

- Video 15-pin D-sub

Cables D-Sub Video cable(fixed), power cord

Regulatory approvals

• TCO '03

MPR-II Low Emission

TÜV/GS,TÜV/Ergo

FCC-B, UL, CSA, DHHS

· SEMKO, Poland-B sign, C-Tick

• CE, BSMI, PSB

NÚTEK, Énergy Star

Physical specifications

Dim. incl. base (WxHxD)
Dim. incl. base (WxHxD)
Dim. excl. base (WxHxD)
15.6" x 13.1" x 16.7" inch
Weight
15.8 kg

Power supply Please refer to rating label
Temperature (operational) 0°C to 40°C/ 32°F to 104° F
Temperature (storage) -25°C to 65°C/ -13°F to 149°F

Relative humidity
MTBF
75,000 H

As an Energy Star partner, Philips has determined that this product meets the Energy Star guidelines for energy efficiency. Microsoft and Windows are registered trademarks of Microsoft Corporation.

MacOS is a registered trademark of Apple Computer, Inc.

All data subject to change without notice Release date: January 2004 www.philips.com